MINISPECTOR® TECHNICAL SPECIFICATION





ACCURATE

MOBILE

Built-in 3D Photo Realistic Cloud (PRC) for highly accurate subsea measurement



STABLE

Seven horizontal and vertical thrusters



Part of the MCS Group mcsoil.com

OVERVIEW

Our **MiniSpector®** mini ROV has been developed and built in-house to provide a small, nimble underwater inspection and metrology drone. Its ability to withstand higher currents than other similar systems on the market means it can deliver tasks normally carried out by larger inspection ROVs.

In-built 3D Photo Realistic Cloud (PRC) technology means the MiniSpector® provides highly accurate measurements to the nearest millimeter and degree.

OUR APPROACH

MiniSpector® applies the latest hardware, software and vehicle control to perform a wide range of inspection tasks. It can be launched from a platform or small vessel and has significantly lower power requirements than a larger ROV.

FEATURES AND CAPABILITIES


- · Foam-less design.
- Dual direction inspection.
- · Umbilical fiber optic.
- Payload up to 14Kg.
- Embedded PRC System.
- Withstands up to 3kts current.
- Auto depth control.
- Auto heading control.
- Pitch hold and Roll hold controls.
- Embedded Cathodic Protection System.

BENEFITS


- It's easy to transport, deploy and power resulting in a flexible solution which saves money.
- High levels of accuracy and 3D technology gathers precise information for planning, construction and maintenance.
- Seven vertical and horizontal thrusters provide full control, stability and maneuverability.

TO PERFORM THE INSPECTION TASKS:


- HD GVI / CVI.
- 3D Photo Realistic Cloud (PRC).
- Contact / Proximity CP.
- UT (Ultrasonic thickness reading).
- Cleaning to bare metal.
- Marine growth removal.




mcsoil.com ______1



Side View 850 mm —



Front View 851 mm -




Top View 851 mm —

Control Console case


- Display
 24" FHD
 1600 nits, sunlight readable
 - Rugged, IP66
 Camera View, Video Overlay.
 - Weight: ~10 Kg
- Tablet
 - 12.5" FHD
 - 1200 nits, sunlight readable
 - Rugged, IP65
 - Pilot software
 - 329.5 × 238 × 24 mm
 - Weight: 1.8 Kg






Case

- Dimensions: 32.5" × 21" × 15.8"
- Weight: 11.36 Kg
- Wheeled, Rugged, IP67



Hand Control Unit

- Dimensions: 263 × 147 × 110 mm
- Weight: ∼1 Kg
- IP65
- Full control 6 DOF
- Camera Tilt/PAN
- Manipulator control



VEHICLE DIMENSIONS

DEPTH		
Payload	14 kg	
Weight	45 kg	
Width	851 mm	
Height	525 mm	
Length	850 mm	

Depth	300 msw
Tether Length	300 m
POWER	

POWER		
Propulsion	8 KW	
Max. Surge, heavy and sway velocity	3 kts for each	
Max. bollard thrust	Surge ±38 kgf Sway ±38 kgf Heave −30 -> 50 kgf	
Maneuverability	6 D.O. F	
Power Source	220 VAC - Single Phase - 50/60 HZ	

PAYLOAD

- Outland MP-100 Manipulator
- Cathodic Protection Probe.
- Ultrasonic Thickness Reading (UT)
- 3D Blue View Sonar
- 2D Imaging Sonar
- Z-T Caviblaster Gun
- Brush Cleaning Tool
- Flooded Member Detection

CAMERA

Camera 1	Colored camera, detachable PAN/Tilt/Zoom (FHD)
Camera 2	Colored Camera, Fixed (HD)
Photogrammetry	 2 x Embedded HD Cameras MCS Solution Photo Realistic 3D Cloud of Points (PRC) MCS Computer Vision

THRUSTERS

- 7 Tecnadyne thrusters providing full control on 6 D.O.F
 - 4 Horizontal thrusters for surge, sway, and yaw
 - 3 Vertical thrusters increasing vehicle maneuverability, stability, and payload capabilities

SENSORS

- All angel depth sensor
- Advanced AHRS providing Heading, Pitch & Roll
- Doppler velocity log (DVL) Sensor

AUTO FUNCTION

- Auto heading, auto depth, pitch hold and roll hold
- AI, Collision Avoidance

OPERATION

- MINISPECTOR ON-Deck station
- Vehicle launch and recovery system
- Tether management system





mcsoil.com/contact-us